

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-6 (cancelled)

Claim 7 (currently amended): A method for auto-exposure control, comprising:

~~determining a presence of artificial illumination in the scene;~~

determining a frequency of intensity variations in the a scene by measuring

contrast variations in the scene;

determining that the scene is illuminated with an artificial illuminant if the contrast variations in the scene exceed a predetermined value;

~~synchronizing an exposure rate with the frequency of intensity variations in the scene;~~

taking at least one exposure of the scene commencing at a preselected phase in the contrast variations ~~the synchronized exposure rate;~~ and

determining at least one exposure parameter for the scene using the at least one exposure.

Claim 8 (currently amended): The method of claim 7, wherein ~~where~~ the presence and frequency of intensity variations of the artificial illumination is determined by user input.

Claim 9 (currently amended): The method of claim 7, wherein ~~where~~ the presence and frequency of the artificial illumination is determined by measuring the light from the scene for periodic changes.

Claim 10 (currently amended): The method of claim 9, wherein ~~where~~ the periodic changes are variations in brightness.

Claim 11 (cancelled)

Claim 12 (currently amended): The method of claim 7, wherein ~~where~~ the frequency intensity variations of the artificial illuminant ~~illumination~~ is determined by the geographic location of the scene.

Claim 13 (currently amended): The method of claim 7, wherein ~~where~~ the exposure parameter comprises an exposure length.

Claim 14 (currently amended): The method of claim 7, wherein ~~where~~ the exposure parameter comprises ~~[[a]] gain [[factor]]~~.

Claim 15 (currently amended): The method of claim 7, wherein ~~where~~ the exposure parameter comprises an aperture size.

Claim 16 (currently amended): The method of claim 7 further comprising ~~[[:]]~~ taking a final exposure, using the exposure setting, at the synchronized exposure rate.

Claim 17 (currently amended): The method of claim 7 further comprising ~~[[:]]~~ taking a final exposure, using the exposure setting, ~~where~~ wherein the final exposure is centered at the cross-over point in the intensity variations.

Claim 18 (currently amended): A method for auto-exposure control, comprising:  
predicting at least one frequency for a variation in the illumination in the scene;  
measuring light from the scene at a periodic rate, ~~where~~ wherein the periodic rate is different than any of the predicted frequencies, using an exposure length that is different than any of the periods of the predicted frequencies;

detecting the presence of an artificial illuminant when the measured light from the scene contains periodic changes;

determining the phase and frequency of the periodic changes with ~~FFT~~ fast Fourier transform analysis of the ~~sampld~~ measured light;

synchronizing an exposure time rate with a phase angle associated with the frequency of the intensity variations in the scene;

taking at least one exposure of the scene at the synchronized exposure time rate, the at least one exposure having an exposure length;

determining at least one exposure parameter for the scene using the at least one exposure.

Claim 19 (currently amended): The method of claim 18, wherein where the exposure length is centered at a crossover point in the intensity variations.

Claim 20 (currently amended): The method of claim 19, wherein where a final exposure is taken, using the exposure parameter, and the final exposure is centered on a crossover point in the intensity variations.

Claim 21 (original): A method for auto exposure control, comprising:

predicting a frequency for a variation in the illumination in the scene;  
measuring light from the scene at a periodic rate using a first exposure length that is equal to the period of the predicted frequency;

re-measuring light from the scene at a periodic rate using a second exposure length that is equal to the period of a second predicted frequency;

determining the presence and frequency of the variation in the illumination in the scene when the variability of the measurements using the first exposure length is different than the variability of the measurements using the second exposure length;

synchronizing an exposure rate with the frequency of the intensity variations in the scene;

taking at least one exposure of the scene at the synchronized exposure rate, the  
at least one exposure having an exposure length;  
determining at least one exposure parameter for the scene using the at least one  
exposure.

Claim 22 (currently amended): An apparatus for auto-exposing a scene comprising:

- a means for measuring light from the scene at a periodic rate using a  
predetermined exposure time;
- a means for determining the presence and frequency of intensity variations of an  
artificial illuminant in the scene by examining the measured light from the scene for  
periodic intensity variations;
- a means for determining exposure parameters for the scene synchronized with  
the frequency of intensity variations.

Claim 23 (original): A digital camera comprising:

- a photo sensor array, the photo sensor array configured to measure light from a  
scene at a periodic frequency using a predetermined exposure length;
- a lens configured to focus the light from the scene onto the photo sensor array;
- a processor, the processor configured to determine the frequency of intensity  
variations in the illumination of the scene by examining the measured light from the  
scene for periodic contrast variations, the processor also configured to synchronize at  
least one exposure, used in an auto-exposure control, to the intensity variations in the  
scene.

Claim 24 (currently amended): The digital camera of claim 23, wherein ~~where~~ a final  
exposure is taken synchronized to the intensity variations in the scene.

Claim 25 (currently amended): A method for auto-exposure control during capture of a  
scene by an imaging device, said method ~~[[,]]~~ comprising:

- determining a presence of artificial illumination in the scene;

determining a period of intensity variations in the artificial illumination ~~[[scene]]~~;  
setting an exposure length equal to an integer multiple of the period of the  
intensity variations in the scene;  
taking at least one first exposure of the scene using the exposure length;  
determining at least one exposure parameter for the scene using the at least one  
first exposure ~~[[.]]~~ ; and  
taking a second exposure using the exposure parameter, wherein the second  
exposure is centered at a cross-over point in the intensity variations.

Claim 26 (currently amended): The method of claim 25, wherein ~~where~~ the presence  
and period of the intensity variations ~~are artificial illumination~~ is determined by user  
input.

Claim 27 (currently amended): The method of claim 25, wherein ~~where~~ the presence  
and period of the intensity variations ~~are artificial illumination~~ is determined by  
measuring the light from the scene for periodic variations.

Claim 28 (currently amended): The method of claim 27, wherein, ~~where~~ the intensity  
variations ~~periodic changes~~ are variations in brightness.

Claim 29 (currently amended): The method of claim 27, wherein ~~where the light from  
the scene is focused onto a photo sensor and the~~ intensity variations ~~periodic changes~~  
are variations in contrast.

Claim 30 (currently amended): The method of claim 25, wherein ~~where~~ the period of  
the artificial illumination is determined by the geographical location of the scene.

Claim 31 (currently amended): The method of claim 25, wherein ~~where~~ the exposure  
parameter comprises an exposure length.

Claim 32 (currently amended): The method of claim 25, wherein ~~where~~ the exposure parameter comprises a gain factor.

Claim 33 (currently amended): The method of claim 25, wherein where the exposure parameter comprises an aperture size.

Claim 34 (currently amended): The method of claim 25 further comprising ~~[[:]]~~ taking a final exposure ~~[[.]]~~ using the exposure parameter ~~setting~~ and using the exposure length.

Claim 35 (cancelled)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**